

AP-LED

Display Lighting

- Using Philips Rebel LED's we can supply with clear or satin diffuser, with or without optical lenses. Cool, neutral, or warm white, RGB or red or blue LED's.
- Dimming options include Mains, 1-10v and DALI with DMX for the RGB option.
- AP-LED CWR (ceiling or wall mount with remote driver).
- AP-LED SR (suspension with remote driver).
- AP-LED CW (ceiling or wall mount) driver built in.
- AP-LED S (Suspension) driver built in.
- Please note RGB always requires a remote driver.



Driver built in



For product support Freecall 1800 733 113 or Email info@yld.com.au

Please see over for installation/instructions.

AP-LED

Display Lighting

TECHNICAL INFORMATION:

LED

Philips Luxeon Rebel, typical LED life 50,000 hours. White available in 3000k 4000k or 6000k, RGB and other LED colours available to order.

FIXING

The AP-LED can be wall and ceiling mounted or suspended from wires, currently all versions have remote drivers only, integral driver version to follow.

CONSTRUCTION

Polycarbonate diffuser, aluminium housing, electronic driver.

OPERATION TEMPERATURE

-25 – +50°C note LEDs will have a reduced lamp/driver life at higher temperatures.

For indoor use only.



STANDARDS

Diffuser 850c GWT

Class 1 or Class 2 with remote driver product EN55015 EN61547.

EN61000-3-2 EN60598-2-1

Covers EMC/LV requirements, CE WEEE and ROHS compliant.

**For product support Freecall 1800 733 113
or Email info@yld.com.au**



Standard End Cap



Integral Driver



Ceiling Wall or Suspension

LED-AP CWR (Ceiling or Wall Mount Remote Driver)

Part no's	Length	Wattage	Forward Voltage	Driver
AP-LED 8CWR	825mm	8.4w	24v	1 x Switched or dimmable Dali, 1-10v or Mains
AP-LED 12CWR	1225mm	12.6w	36v	1 x Switched or Dimmable Dali, 1-10v or Mains
AP-LED 16CWR	1645mm	8.4w x 2	24v x 2	2 x Switched or Dimmable Dali, 1-10v or Mains
AP-LED 24CWR	2445mm	12.6w x 2	36v x 2	2 x Switched or Dimmable Dali, 1-10v or Mains

LED-AP SR (Suspension Remote Driver)

Part no's	Length	Wattage	Forward Voltage	Driver
AP-LED 8SR	825mm	8.4w	24v	1 x Switched or dimmable Dali, 1-10v or Mains
AP-LED 12SR	1225mm	12.6w	36v	1 x Switched or Dimmable Dali, 1-10v or Mains
AP-LED 16SR	1645mm	8.4w x 2	24v x 2	2 x Switched or Dimmable Dali, 1-10v or Mains
AP-LED 24SR	2445mm	12.6w x 2	36v x 2	2 x Switched or Dimmable Dali, 1-10v or Mains

Add colour to the part number.

White options 3000k 4000k or 6000k

Colour options Red, Blue or green

Colour change RGB 24CW requires two drivers 12CW or 24CW lengths only, supplied with 5m cable, Longer cables to order.



Fixing brackets for wall or ceiling mount with remote driver.