

AP-T5

Display Lighting

- Available in HE (High Efficiency) or HO (High Output) with a choice of switched or dimmable 1-10v, DSI or DALI protocols. The AP-T5 is supplied with satin diffuser and a reflector for maximum light output.
- DDP coloured sleeves can be fitted to the HE version only, there are fifteen colours to choose from.
- A choice of three end caps, AP-T5 CW (ceiling or wall) mount, or AP-T5 S (Suspension) offers great versatility.
- Photometric data available.



Standard



Option 1



Option 2

Optional End Caps increase length by 42mm

For product support Freecall 1800 733 113 or Email info@yld.com.au

Please see over for installation/instructions.

AP-T5

Display Lighting



TECHNICAL INFORMATION:

LAMP

T5 14-35w or 24-80w colour 840 cool white, typical lamp life 20,000 hours. Other lamp colour temperatures available.

FIXING

The AP-T5 Stick can be wall and ceiling mounted or suspended from wires.

COLOURS

Any lamp colour or DDP coloured sleeve (guaranteed fade free can be specified for the HE 14w 21w 28w or 35w lamps, coloured sleeves are not suitable for the HO 24-80w lamps.

Ice blue, sky blue, royal blue, purple, lavender, candy pink, pink, light red, red, orange, light orange, chrome green, leaf green, acid yellow and candlelight.

Other colours available but not guaranteed fade free.

CONSTRUCTION

Polycarbonate diffuser, aluminium lamp housing, steel reflector and ballast housing, electronic ballast and T5 lamp.

STANDARDS

Diffuser 850c GWT.
Class 1 product EN55015 EN61347.
EN61000-3-2 EN60598-2-1.
Covers EMC/LV requirements, CE WEEE and ROHS compliant.

OPERATION TEMPERATURE

Switched -15 – +50°C.
Dimmable +10 – +50°C.

Note lamps will operate at reduced light output at lower temperatures and reduced lamp/ballast life at higher temperatures.

For indoor use only.



Switched or Dimmable DALI, DSI or 1-10V.
Satine diffuser 827,830, 840 or 865 lamp.
DDP coloured sleeves only suitable for HE lamps.

AP-T5 CW (Ceiling or Wall mount)		
Product Code	Wattage	Length
AP-T5 14CW	14wHE	600mm
AP-T5 21CW	21wHE	900mm
AP-T5 28CW	28wHE	1200mm
AP-T5 35CW	35wHE	1500mm
AP-T5 24CW	24wHO	600mm
AP-T5 39CW	39wHO	900mm
AP-T5 54CW	54wHO	1200mm
AP-T5 80CW	80wHO	1500mm

AP-T5 S (Suspension)		
Product Code	Wattage	Length
AP-T5 14S	14wHE	600mm
AP-T5 21S	21wHE	900mm
AP-T5 28S	28wHE	1200mm
AP-T5 35S	35wHE	1500mm
AP-T5 24S	24wHO	600mm
AP-T5 39S	39wHO	900mm
AP-T5 54S	54wHO	1200mm
AP-T5 80S	80wHO	1500mm

For product support Freecall 1800 733 113 or Email info@yld.com.au